

Technical Datasheet

Art.-Nr. 2020203405



WEPOS Stone Sealer

Description

Forms a waterproof, UV-resistant and silky gloss protective layer. The surface is water- and stain-resistant and stronger in colour and structure. The surfaces are easier to maintain. The protective layer is non-yellowing and durable. For all absorbent natural and artificial stone surfaces indoors and outdoors.

Effect:

Forms a waterproof, UV-resistant and shiny satin protective layer. The surface becomes more resistant to dirt, and its color and texture are reinforced. The stone's appearance is visibly improved. Water and dirt can no longer permeate the surface, and the surface is easier to care for. The protective layer is non-yellowing and durable.

Application:

For all absorbent natural and artificial stones, concrete building blocks, exposed aggregate concrete, slate, marble, sandstone, terrazzo, porphyry, Solnhofen slabs, concrete surfaces, etc. Can be used indoors and out, for floors, steps, terraces, balconies and windowsills.

Direction of use:

The base needs to be dry, unmarked and clean. Apply a thin, even layer using a paint roller or a brush. Do not apply more than the surface can absorb, and avoid leaving puddles. Avoid creating streaks. Drying time is about 2 hours. Do not step on the surface during this time. Afterward, protect the sealed surface from moisture for 2 days.

Important:

Surfaces must be dry before applying sealant. White marks that appear after drying indicate moisture in the stone. Application areas must also be protected from moisture from underneath. For larger surfaces, always work in sections. Cover glass and solvent-sensitive materials during the application. Do not process at temperatures below 12°C. Surfaces that are non-absorbent, polished or finely smoothed cannot be sealed.

Technical Informations

- Density: 1,03 g/ml
- PH: 8,0 – 8,5
- colour: milky
- smell: flowery

Safety instructions:

Flammable

Harmful

Dangerous for the environment

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Keep out of the reach of children.

Do not breathe spray.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

Packing unit

1000 ml-bottle (4 per box)

Please beware of: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. The liability of WEPOS for defective products and any claims for damages whatever is limited to the purchase price of the products. WEPOS shall not be liable for any consequential damages. No other warranty or representation is made or implied.

April/13