



Snickerigrund Classic

Product description:

Snickerigrund Classic is a primer for painted or previous not painted wood indoors, but also on sanded matt laminate, tiles and factory painted surfaces.

The product is a thixotrope primer with the highest demand on application, levelling, grind ability and richness. Good adhesion to metal and wood surfaces, and even more difficult surfaces.

The product is also suitable as primer for absorbing textile wall papers.

TECHNICAL DATA:

Area of application	Indoors
Binder	Alkyd
Volume Solids	46%
Density	1,43 g/cm ³
Gloss	Matt
Thinner/Cleaning	White spirit
Material consumption	5–10 m ² /L
Temperature at painting	Minimum. +5°C
Tools for painting	Brush, roller and (after dilution) spray
Dust dry	2–4 h
Re-paintable	24–36 h
Completely dry	72 h
Shelf life	2 years if unopened, frost free storage
Colour	White
Flammability	3
VOC category	(Cat. A/d): 300 g/l (2010)



Snickerigrund Classic

How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint.

The use of correct tools and a carefully performed base is the foundation for a successful result. Do not paint if it is below +5°C.

Make sure to protect floors and furniture before starting to paint.

The surface must be clean, dry and firm. Wash, rinse with water and let dry. If there are oil stains, they can be removed with solution. Not previous treated wood is to be primed with Snickerigrund Classic diluted 10–20%. If the surface is uneven, fill with putty and grind. Apply undiluted Snickerigrund Classic, grind, apply and so on until there is an even and smooth surface. Wipe clean.

Painting

Prime 1–2 times with sufficient drying time between. Top coat with suitable paint.

Use brush, lint free roller, or – after dilution – sprayer.

This product has a very high dry solids content which provides very good filling and covering ability.

Post-painting

Wipe off the tools thoroughly before cleaning with White spirit. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.