

Declaration of Performance No

175/1/CPR



|                                                                               |                                                                                                                                                          |
|-------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Unique identification code of the product-type:                               | ATLAS GTA (2020)                                                                                                                                         |
| Intended use or uses:                                                         | Use on internal walls, ceilings, columns and partition walls.<br>General construction.                                                                   |
| Manufacturer:                                                                 | ATLAS sp. z o.o.<br>ul. Jana Kilińskiego 2, 91-421 Łódź, Poland<br>telefon: +48 (42) 631 89 45<br><a href="http://www.atlas.com.pl">www.atlas.com.pl</a> |
| System or systems of assessment and verification of constancy of performance: | System 3<br>Notified body No. 0767 MPA Dresden GmbH                                                                                                      |
| Harmonized standard:                                                          | EN 15824:2017<br>EN 13963:2005<br>EN 13963:2005/AC:2006                                                                                                  |

Declared performance:

| Essential characteristics        | Performance |
|----------------------------------|-------------|
| Adhesion                         | 0,3 MPa     |
| Thermal conductivity coefficient | NPD         |
| Reaction to fire                 | A1          |
| Dangerous substances             | NPD         |

| Essential characteristics              | Performance |
|----------------------------------------|-------------|
| Reaction to fire (for direct exposure) | A1          |
| Flexural strength                      | 350 N       |

The performance of the product is in conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by: Patrycja Stasiak in Łódź, 08.02.2022.

ATLAS sp. z o.o.  
Dyrektor ds. Jakości  
*Stasiak*  
Patrycja Stasiak