



Våtrumsspackel LV

Product description:

VÅTRUMSSPACKEL LV is a water-borne putty for general use, based on copolymer. Easy to work with.

Range of use: VÅTRUMSSPACKEL LV is suitable for putty work in wet rooms indoors and fulfil the demands for those.

The product fulfil the demands for M1 and CE marking according to EN 15824:2009 and EN 13963:2005.

TECHNICAL DATA:

Colour	blue grey
Solvent	water
Filling capabillity	max 4 mm
Grain size	max 0,15 mm
Dry substance	approx. 61 %
Density	approx. 1 100 kg/m ³
Application	manually
Drying time	1 hour per mm, longer for thicker layers. The drying time can vary depending on the base, temperature, air humidity etc.
Adherence	the product has a high tack against concrete and plaster.
Temperature of use	+5°C - +35°C
Cleaning of tools	water



Våtrumsspackel LV

WORKING INSTRUCTIONS

Prepare the basis before bonding so that it becomes even and firm. Important that the surface temperature is not less than +5°C.

Use a steel spatula for applied the putty. The drying time can vary depending on the base, temperature, air humidity etc.

When sandpapering putty, use eye-protection and a face protective mask. The grounded surface shall be dusted before further processing. See the directions given by the paint manufacturer.

For cleaning of tools use lukewarm water before the putty has dried.

