



## DIMENSION

TECHNICAL PRODUCT DATA SHEET

2022-10-26

Page 1/2

### Product description:

Dimension is a glossy, solvent-based and durable floor paint for indoor use. Due to the scratch- and water-resistant surface, the paint is excellent as enamel paint as well. The paint can be used on different types of wooden floors, linoleum, metal and concrete. Thanks to its flexibility Dimension can be applied to a variety of substrates with good results. Use a brush, lint free roller, pad or (after dilution with white spirit or naphtha) sprayer. The paint is based on urethane alkyd which has very good qualities in terms of adhesion, resistance to water, scratches, impact, weather, alkali, etc.

Dimension is produced in Sweden and is included in the Colorex Mix tinting system.

### TECHNICAL DATA:

Area of application	Indoors
Binder	Urethane alkyd
Volume Solids	46%
Density	1,11 kg/L (white-base)
Gloss	80 (glossy)
Washability	Class 1
Thinner/Cleaning	White spirit
Material consumption	8–12 m <sup>2</sup> /L
Temperature at painting	Minimum +5°C
Tools for painting	Brush, roller and (after dilution) sprayer
Dust dry	4–6 h
Re-paintable	18–24 h
Completely dry	24–72 h
Colour	White
Flammability	2b
VOC category	(Cat. A/i): 500 g/l (2010)



# DIMENSION

TECHNICAL PRODUCT DATA SHEET

2022-10-26

Page 2/2

## How to use

### Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint. The room temperature is important too for the end result. Do not paint if it is below +5°C. The surface must be clean, dry and firm. Brush or scrape away loose old paint. Sand and wash previously painted surfaces with appropriate cleaner and rinse with water.

Concrete floors: Fresh concrete must temper approximately one week before treatment. Any laitance must be removed before painting. The product shall be diluted with 30–50% white spirit. Prime untreated wooden floor with Dimension diluted with 20% white spirit. Second coat without dilution. Remember to protect the surrounding thoroughly before beginning to paint.

### Painting

Paint at least 2 times with undiluted Dimension for full coverage with roller, brush, or – after dilution with white spirit – with sprayer.

### Post-painting

Wipe off the tools thoroughly before cleaning with white spirit. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

### Maintenance

Use a cloth dampened in water and possibly some mild cleaning liquid to clean the surface. Never use spirits when cleaning painted or lacquered surfaces.